

Pre Delivery Inspection - Checklist				
Model:	XSM 125/XTM 125		VIN:	
Dealer:			Engine no.:	
Place:			Battery no.:	
Assembly	No	Check	Notes	Remarks
VIN / Engine no.	1	Check VIN/engine number on the vehicle and in the documents		
Battery	2	Check voltage/recharge	Min. 12.5 V, ow. recharge	
Fuel	3	Fill some fuel	Min. for test ride	
Aesthetic inspection	4	Visual inspection of all visible parts for optical defects/gap dimensions□	Paintwork/fitting of plastic parts/scratches/dirt	
Tightening torques inspection	5	Safety fasteners: - Front- and rear suspension unit - Front and rear brake caliper retainer unit - Front- and rear wheel unit - Engine-chassis retainers - Steering assembly	Check whether screws are provided with markings! If not, check the tightening torques according to the Service Manual!	
	6	Plastic parts fixing screws	Check for tightness!	
Electrical system	7	Main switch	Check function	
	8	High beam, low beam, position light incl. indicator lamps	Check function	
	9	Headlight adjustment	Check	
	10	Brake light and brake light switches front and rear	Check function	
	11	Turn indicators and their indicator lamps	Check function	
	12	Instrument panel lights	Check function	
	13	Fuel and temperature indicator	Check function	
	14	Indicator lamps on instrument panel	Check function	
	15	Horn	Check function	
	16	Electric starter	Check function	
	17	Engine stop via emergency stop switch and side stand	Check function	
Levels check	18	Brake fluid front and rear	Fill level check	
	19	Coolant	Fill level check	
	20	Engine oil	Fill level check	
Road test	21	Cold start	Engine starts up easily	
	22	Instrument panel operation	Check function	
	23	Throttle control	Check response	
	24	Accelerating and braking	Check stability	
	25	Front and rear brake	Check efficiency	
	26	Front and rear suspension	Check efficiency	
	27	Abnormal noise		

Static test	28	Restarting when warmed up	Immediate startup	
	29	Elektric and kickstarter (if present)	Check function	
	30	Turning of steering	Smooth-running	
	31	Possible leaks	Check	
	32	Electric fan	Check function	
Functional inspection	33	Hydraulic braking system		
	34	Clutch travel	Empty travel at lever end: 10 - 15 mm	
	35	Rear brake lever travel	Minimum distance: 1 mm	
	36	Clutch	Check correct operation	
	37	Engine	Check for correct general operation and absence of abnormal noise	
	38	Other		
	39	Documentation	Check completeness	
	40	License plate fitting	Check	
	41	Main, steering, fuel cap, seat lock etc.	Check function	
	42	Tyre pressure check	Front: 1,9 bar; rear: 2,1 bar	

Date:	Dealer: Seal, name, signature	Customer: Name, signature