



Liquid-cooled single-cylinder four-stroke engine with two intake valves and two exhaust valves

## POWER TRANSMISSION

Clutch type	Multi-disc oil bath clutch
Gearbox	6 speed manual transmission

### CHASSIS

Frame type	Tubular steel loop frame
Front suspension	Upside-Down fork
Standpipe diameter	41 mm
Compression and rebound damping	not adjustable
Rear suspension	Central suspension strut
Spring preload	not adjustable
Compression and rebound damping	not adjustable
Swing type	Two-arm swing arm
Steering head angle	26°
Caster	111 mm
Front suspension travel	
Rear suspension travel	170 mm

#### BREAKING SYSTEM

Safety system	ABS
Front brake disc	one brake disc, perforated, Ø 260 mm
Front brake caliper	Two-piston floating caliper
Rear brake disc	one brake disc, perforated, Ø 218 mm
Rear brake caliper	Single-piston floating caliper

#### **WHEELS**

Front rim type	Snoked rim
Front rim size	
Front tire size	
Rear rim type	
Rear rim size	
Rear tire size	
Standard tires	CST CM-731

#### **DIMENSIONS**

Length	2.140 mm
Width	
Height	1.220 mm
Wheelbase	1.425 mm
Seat height	. 910 mm
Ground clearance	. 300 mm

## WEIGHTS

Unladen weight ready to drive	124 kg
Maximum permissible front axle load	111 kg
Maximum permissible rear axle load	179 kg
Maximum permissible total weight	290 kg
Maximum permissible payload	166 kg

### DRIVING PERFORMANCE

Maximum speed	99 km/h
Fuel tank capacity	
Fuel consumption	3,0 L/100 km
Range	
Gradeability	18%
Number of seats	

### **FEATURES**

LED headlight; LED turn signal; LED taillight; LCD display

# AVAILABLE COLOURS

Neve White

#### APPROVAL OPTIONS

Vehicle class	L3e-A1
Homologation number	e13*168/2013*01739*00
Variant	
Version	3